

# ECP-LED4 LED RANGE



## TECHNICAL SPECIFICATIONS

<b>MODEL NO:</b>	<b>ECP-LED4</b>
Mode of Operation:	Maintained / Non-Maintained
Lamp Type:	AC LED Tube 180-240 Volts AC, 22W (max)
Rated Duration:	1hours / 2 Hours
Mains Supply:	220-240 Volts, 50-60Hz
Supply Current:	30mA
Power Consumption:	3W
Battery Charger:	Regulated variable rate
Battery Protection:	Low battery voltage cut off to prevent over discharge
Battery Type:	High Temperature Li-ion (LiPoFe4)
Charge Monitor:	LED
Test Facility:	Momentary test switch
Casing Construction:	Electro-galvanised steel
Max. Casing Temp, Tc:	70°C
Max. Ambient Temp, Ta:	50°C

## Ordering Guide:

Ordering Code	Battery Type	Battery Configuration
ECP-LED4/240/12.8/1.5AH	Li-ion 12.8V/1.5AH	Cane
ECP-LED4/240/12.8/3.2AH	Li-ion 12.8V/3.2AH	Cane

## OUR ECP-LED CONVERSION KIT IS SUITABLE FOR A WIDE RANGE OF LED FITTINGS

- AC LED Load
- Suitable for a wide range of AC LED Tube, Down lights.
- Short-circuit protection at battery terminals.
- Extra low standby power consumption.
- Able to power a LED light fitting at a reduce luminous flux for two hours or more
- High Temperature 70 °C Li-Ion battery
- Automatically activated in the event of power cuts
- Offer a good luminous flux to facilitate the evacuation.



CLASS I

