

CMZ2EX-UPS

EXPLOSION PROOF

MAINTAINED / NON-MAINTAINED EXPLOSION
PROOF EMERGENCY EXIT LUMINAIRE



Ordering Guide:

Ordering Code

CMZ2EX-UPS






- Made of stainless steel body, bolts and nuts, meeting IP66 ingress protection.
- Surface mounted, comes complete with mounting accessories.
- Suitable for maintained and Non maintained operation with central battery systems with wide AC or DC output.
- Explosion proof construction meeting the requirements of EN 60079-0: 2012+A11: 2013, EN 60079-18: 2015, EN 60079-1: 2014, EN 60079-28: 2015, EN 60079-7: 2015, EN 60079-31: 2014, IEC 60079-0: 2017, IEC 60079-1: 2014-06, IEC 60079-7: 2015, IEC 60079-18: 2014, IEC 60079-28: 2015, IEC 60079-31: 2013

TECHNICAL SPECIFICATIONS

MODEL NO:	CMZ2EX-UPS
Mode of Operation:	Maintained or Non Maintained
Lamp:	12W White LED
Type :	Single sided, surface mounted
Supply Mains	220-240V AC 50/60Hz
Emergency Supply (UPS) :	220-240V AC 50/60Hz, 150-300V DC
Current Consumption:	< 0.15
Fitting Construction:	Stainless steel
Fitting Dimensions :	260 x 360 x 150mm
Protection :	IP66
Relevant Standards :	IEC 60598-2-22

***Note: Technical Specification subject to change without prior notice

Pictogram Options (add suffix to model Number)

empty	=		(EXIT)
/S	=		(exit left)
/D	=		(exit right)
/G	=		(exit straight ahead)
/T	=		(transparent)

DIMENSIONS:

